

Offer

330/24

Date

28/05/2024

Customer

SC TERRA MACHINES SRL

Validity

27/06/2024

Address

 TERGU NEAMT
 PETRA NEAMT
 ROMANIA

Model

SMART 30

Reference

Mr. Barbu Neculai

Offer

1

S30

CNC WORKING CENTER SMART 30

CNC machine mod. SMART 30 with fixed working table and open bridge suitable for woodworking, multi-layers, medium density, plastic materials, thermoformed and other similar materials.

STRUCTURE

The structure is composed by fixed working table and open bridge that allows to occupy at least the space available as the movements in X, Y and Z are carried out by the mobile portal where the operating heads and any aggregate groups are installed.

The pieces are always fixed to the table, as movements along the three axes X, Y and Z are carried out by the head carriage and the operating head.

The base frame and the head carriage are made of electric welded steel, which is normalized and suitably ribbed in order to obtain maximum stiffness and long-lasting life.

The X axis movement is carried out on a high precision rack system, while the Y and Z axis movement is carried out by means of threaded worm screws coupled to high precision and high reliability preloaded ball lead nuts with slack recovery.

All slidings run on linear guides with prismatic geometry fitted with ball circulation tracks coupled to high precision preloaded slides.

The screws are driven by brushless motors to achieve the best finish and long-term reliability.

Positioning accuracy is ensured by **ROTARY ENCODERS** with coaxial resolution set to +/- 0.05 mm. and angular resolution set by + / 0.0019 °.

TECHNICAL DATA

Quick speed X-axis: 60 m/min

Quick speed Y-axis: 60 m/min

Quick speed Y-axis: 60 m/min
Quick speed Z-axis: 15 m/min
vectorial speed 85 m/minute
Stroke X-axis: 3550 mm
Stroke Y-axis: 1790 mm
Stroke Z-axis: 430 mm

Max passage piece with bar top 120 mm
Max passage piece with Cosmec table 150 mm
Working area: 3100 mm. x 1350 mm.

Working pressure 7 bar
Suction nozzle 200 mm
Air consumption per suction 2650 mc / h

The machine does not require particular environmental conditions: it must be installed inside an illuminated, ventilated building with a solid and level floor.

VACUUM SYSTEM

The system controls both working areas for pendular loading/unloading operations. It is equipped with vacuum pressure switches that permit monitoring of the level achieved in each area and consequently the clamping of the pieces to be machined. Properly sized electrovalves connected to the relevant vacuum tanks, built-in in the structure of the machining centre, assure the connection to the pump.

LUBRICATION

The machining centre is equipped with a centralized automatic lubrication system with distribution pump, complete with tank. The system is managed by the CNC with programming of intervention times. The CNC displays messages relating to the achievement of the minimum lubrication level.

PROTECTION SYSTEM

The machine, which is equipped with standard CE NORMS, is provided with safety mats on the front side and a perimetral net with access door, controlled by an electromechanical system.

The safety mats are divided into No.3 working areas:

- right area, that allows the operator to perform safe loading and unloading operations while the machine work cycle operates on the opposite side of the working table.
- left area performs in the same way than the right one.
- On the front of the machine there are two columns with start button to restart the cycle.

The machining centre is provided with a numerical controller, which contains all the functions for proper management of the three encoder axes.

The server-client functions of the controller allow an easy running of complex applications.

The controller programming can be carried out in a simple and guided way by means of a user

The controller programming can be carried out in a simple and guided way by means of a user friendly graphic interface, to automatically generate the part program.

CONTROLLER TECHNICAL DATA

OSAI SERIES OPEN CNC WITH 'ASPAN SE' GRAPHIC INTERFACE

The controller and all electronical components are installed inside the electrical cabinet, while the latest-generation PC (equipped with I-5, I-7 or higher processor) is located on a movable console. This system allows the operator to stay in the most appropriate position to the working requirements.

The machine is equipped with a **MOBILE TOUCH PENDANT** containing the main operating functions of the machine so that it can operate near the workpiece if it is too far from the control console.

Integrated CAD-CAM System

The machine is equipped with an integrated CAM system to facilitate programming of the machine: **ASPAN SE**

is a software of the ASPAN family. Through the use of simple commands, it allows to realize immediately the drawing of a piece to be produced (CAD) and the relative machine program (CAM).

1) CAD:

- Generic commands for drawing (f.i. straight line, arc, circle, polyline, ...)
- Commands to set entity data (f.i. depth, diameter, ...)
- Commands to modify entities (f.i. delete, move, copy, rotate, ...)
- Basic commands for route management (f.i. connection, chamfer, cut, extend, ...)
- Parametric management
- Import / Export DXF file (POINTS, LINES, ARCHES, CIRCLES, POLYLINE, ELLIPSE)
- Management of suction cups working table.

2) CAM:

- Tooling data management (f.i. tool length and diameter, working speed, ...)
- Automatic tool assignment
- Manual drilling assignment
- Manual milling assignment
- Assign milling input / output (f.i. tangent line, tangent arc, ramp in Z, ...)
- Multi-machining (machining with multiple tools on the same geometry)
- Management of manual machining sequence
- 2D simulation
- Generating machine program

3) ASPAN SE can be enriched with the following optional modules:

- Commands to draw 3D entities (f.i. inclined plane, hole / arc / inclined line, ...)
- Nesting (single / multi panel, work list, graphic reports, ...)
- Create / print labels (customizable by the operator)
- 2D vectorializer (conversion from bitmap to vector)
- 3D Artistic CAM (transformation of bitmap to shades of gray into three-dimensional)
- Single panel door management (parametric door realization)

- Single panel door management (parametric door realization)
- Furniture management (parametric realization of furniture and shelves)

ASPAN SE can at any time be upgraded to the most complete version ASPAN PROSPECT.

1 SM 02A

WORKING TABLE WITH 6 BARS AND 12 CUPS + 2 SUPPORTS

The working table, designed for a quick and easy set-up, is composed of:

- No. 06 panel supports (l = 1200 mm)
Each support slides along the X axis on hardened and rectified round bars and 04 ball couplings.
The support locking takes place on the round bars by means of No.2 cylinders, and is controlled by a push-button placed in front of the panel support.
The correct positioning of the movable panel support takes place on a metric scale along the X axis.
Each bar is complete with a reference stop.
- No. 12 jigs (dimensions 120 x 120 x 50 (h) mm) , sliding along the Y axis.
The correct positioning of the jig is guaranteed by the presence of a metric scale on each bar.
Jig locking/unlocking takes place by means of a pneumatic manual unlocking device, located on a side of the jig.
- o. 02 bar supports to facilitate the loading of large and heavy panels. Composed of two blades in scratch-resistant material, it is operated by two pneumatic pistons controlled by the CNC through M codes
- No. 02 side fixed bars, one on the right side and the other on the left side.
- No. 02 reference stops, positioned along the lateral fixed bar, one on the right and one on the left.

1 SM 03B

100 MC/H VACUUM PUMP

100 mc/h vacuum pump. It is driven by a 3.3 Kw three-phase asynchronous motor and creates a vacuum by rotating high-strength abrasive blades
This system guarantees the absence of vibrations and the maximum silence of the vacuum system.
Air cooling guaranteed by a fan installed inside the structure.

1	SM 04A 13,2 KW AIR COOLED ELECTROSPINDLE ISO 30 13,2 kW electrospindle with air cooling system. Rotation on ceramic bearings with permanent grease lubrication. ISO 30 tool holder with automatic connection device and pneumatic release. The power of the spindle motor allows excellent take-off work even at low rpm. TECHNICAL DATA: - 11 kW (15 HP) in class S1 - 13,2 kW (18 HP) in class S6 - ceramic bearings - right and left rotation - CNC programmable rotation speed from 500 to 24,000 rpm Complete with dust hood.
1	SM 04OA TOOL CHANGER 10 POSITION ISO 30 Automatic tool changer system with 10-position tool carousel, installed on the machine portal. - max. no.10 consecutive tools, 150 mm diam. - max. tool diameter: 250 mm - max. tool length: 200 mm - max. no.2 aggregates - max. weight (each tool or aggregate): kg 6 - max. total weight: kg 40 Tool holders are not included.
1	SM 08A TELESERVICE It allows an immediate and direct access to the machine numerical control via modem. This way it is possible to check machine data, user programs, input/output signals and system variables, and to install software updates, therefore granting: . real-time answers . quick problem solving . strong reduction of machine downtime . real-time software updates

TOTAL: € 79.254,00

General terms and conditions of sale

Delivery:

Goods:

Ex-works

Packing:

Not necessary

Test:

COSMEC TECHNOLOGY Loc.Fosci 28 - Poggibonsi (SI) - ITALY

Start-up and training course:

Included

Warranty:

12 months at End-User's site

Payment:

Voltage:

380 V 50 Hz 3 ph. + GND

Pursuant to Article 13 of EU Regulation No. 2016/679 of 04/27/2016, COSMEC TECHNOLOGY SRL, as Data Controller of the processing of your personal data, informs you that the personal data acquired will be processed in compliance with the provisions of current legislation through manual, IT and telematic tools with logic strictly related to the purposes of the processing. The data provided will be used for contractual purposes and also to send you information or notifications. The data collected will not be disseminated, but may be disclosed to the subjects and in the ways indicated by the current legislation. You have the right to access your data at any time, oppose the processing of the same, request the correction, modification and/or cancellation and exercise the right to limit the processing and the right to data portability. For this purpose, you can contact the Controller of the processing: COSMEC TECHNOLOGY SRL - with registered office at Fosci, 28 - 53036 Poggibonsi (SI) - Tel. 0577988010 - info@cosmecsr.com - The complete Privacy Policy on the processing of personal data is available at the Data Controller's website.